



## Hub Dimensions

### **1000E Wedg-Lok® Series Hub—10-Hole**

Hub Length – 7"

Keyed insert to match tractor axle

1 radius insert for wedging hub to axle

4 Jackbolts for removal of inserts

Guide pin for easy alignment of wheel

Approximate Weight –175 lbs.

Torque insert bolts to 400 ft. lbs.

Torque wheel bolts to 400 ft. lbs.

### **2000E Wedg-Lok® Series Hub—10-Hole**

Hub Length – 7"

Keyed insert to match tractor axle

1 radius insert for wedging hub to axle

2 threaded jackscrew holes in each insert for removal

Guide pin for easy alignment of wheel

Approximate Weight –175 lbs.

Torque insert bolts to 400 ft. lbs.

Torque wheel bolts to 400 ft. lbs.

These hubs can be used with the inserts listed below, unless noted otherwise.

	Tractors	Axle Diameter		Tractor Axle Configuration	INSERT NEEDED		
		IN	MM		INSERT CODE	WOLD CODE	WOLD PART NUMBER
		190XT*, D-21, 200, 7000	3/4"		82.55 mm		N/A
<b>Allis-Chalmers, Deutz, Deutz-Allis, &amp; AGCO-Allis</b>	8775,8785,AGCO RT95, AGCO RT115, RT120D, Challenger MT535BD, Challenger MT545BD	3/4"	82.55 mm		KR-13M	27816	WNDH-DADHI-KR0013M
	MT515E, MT525E*, MT535E*, MT545E*, MT555E*, MT565E*, MT575E*	3/4"	82.55 mm		KR-17M		
	210,220,7010*,7020*,7030,7050,8010*,8030*	3 5/8"	92.075mm		KR-20M	27822	WNDH-DADHI-KR0020M
	7020*, 7040, 7060, 7110, 7120, 7580 ,8050, 4W-220	3 3/4"	95.25mm		N/A	N/A	N/A
	9435, 9455,9735*,9745*	3 3/4"	95.25mm		KR-30M	27829	WNDH-DADHI-KR0030M
	DX90,DX110,DX140,DX160,7145,9130 ,9150,9170,9190,9630,9635, 9650,9655,9670**,9675**,9690**, 9695**,9735*, 9745*,9815**	3 7/8"	98.425mm		KK-88M†	62569	WNDH-DADHI-KK0088M
	7080, 8070*, 8550-Rear Axel, 4W-305-Front Axel*, 4W-305-Rear Axle	4"	101.6mm		KR-1450M	27849	WNDH-DADHI-KR1450M
	9670*,9675*,9690*,9695*,9735*, 9745*,9755, 9765, 9775, 9785, 9815*, DT160, DT180, DT180A, DT200, DT200A, DT205B, DT220A, DT225, DT225B, DT240A, DT250B, DT275B, MT585B*, MT585E*, MT595B*, MT595E*, MT635, MT645, MT645C, MT645D, MT645E, MT655, MT655C, MT655D, MT655E, MT665, MT665C, MT665D, MT665E, MT675C, MT675D, MT675E, MT685E, MT685D	4.331"	110mm		KR-80110M	27853	WNDH-DADHI-KR80110M
	RT135D, RT150D, RT100V, RT120V, RT135V, RT150V, RT130, RT145, RT155, MT525BV, MT525E*, MT535BV, MT535E*, MT545E*, MT545BV, MT555BD, MT555BV, MT555D, MT555E*, MT565BV, MT565E*, MT565, MT565D, MT565BD, MT575B, MT575E*, MT575D, MT585B*, MT585D, MT585E*, MT595, MT595B*	3 3/4"	95.25mm		KR-3530M	27852	WNDH-DADHI-KR3530M

\* These model have been produced w/ more than one axle diameter. Please Verify axle diameter w/ customer before ordering.












\*\* These model may have dealer-installed 110mm diameter axel with a straight keyway. KR-80110M will not work with this axle. Other dual options may be available

† To install hub, the two loose keys in the tractor axle must be shortened (cut off)

P.O. Box 129 · St. Ansgar, Iowa 50472 · 641-713-2205 · 1-800-443-9653 · Fax 641-713-4005

	Tractors	Axle Diameter		Configuration	INSERT NEEDED		
		IN	MM		INSERT CODE	WOLD CODE	WOLD PART NUMBER
<b>Case &amp; Case-International</b>	4230, 4240, C70, CX70, C80, CX80, C90, CX90, C100, CX100	2¾"	69.85mm		N/A	N/A	N/A
	970*, 1070*, 1270*, 1370* 1570*, 1896*, 2090, 2094, 2096*, 2290*, 2294*, 2390*, 2394*, 3294, 5120, 5130, 5140, 5220, 5230, 5240, 5250, 7110, 7210, 8910, MX80C, MX90C, MX100C, MX100, MX110, MX120, MX135, MX150	3½"	88.9mm		KR-25M	27825	WNDH-DADHI-KR0025M
	Farmall 110A, Farmall 120A, Farmall 125A, Farmall 130A, Farmall 140A, MXM120, MXM130, MXM140, MXM155, MXU100, MXU110, MXU115, MXU125, MXU135, Maxxum 110, 115, 120, 125, 130, 135, 140, 145, 150, PUMA 115, 125, 130, 140, 145, 150, 155, 160, 165*	3 <sup>5</sup> / <sub>8</sub> "	92.075mm		KR-2920M	27851	WNDH-DADHI-KR2920M
	970*, 1070*, 1270*, 1370*, 1570*, 1896*, 2096*, 2290*, 2294*, 2390*, 2394*, 2590, 2594, 3394, 3594	3 <sup>7</sup> / <sub>8</sub> "	98.425mm		KR-8M	27813	WNDH-DADHI-KR0008M
	7120, 7130, 7140, 7150, 7220, 7230, 7240, 7250, 8920, 8930, 8940, 8950, MX170, MX180, MX200, MX210, MX215, MX220, MX230, MX240*, MX255*, MX245, MX270*, MX275*, MX285*, MX305*, MX335, Magnum 180*, 190*, 200, 210*, 215*, 220, 225, 235, 240, 245*, 250*, 260, 275*, 280, 290*, 305*, STX275, STX280*, STX325, STX330*, Steiger 335*	4"	101.6mm		KR-50M	27833	WNDH-DADHI-KR0050M
	MXM175, MXM190, Magnum 180*, 190*, 210*, PUMA 165*, 170, 180, 185, 195, 200, 210, 215, 220 225, 230, 240, Optum 270, 300	4.13"	105mm		KR-31M	27831	WNDH-DADHI-KR0031M
	9110, 9130, 9150, 9210, 9230, 9250, 9310, 9330, 9350	4"	101.6mm		KR-1450M	27849	WNDH-DADHI-KR1450M
	MX240*, MX255*, MX270*, MX275*, MX285*, MX305*, STX280*, STX330*, STX375, STX380, STX425, STX430, STX440, STX450, STX480, STX530, Magnum 215*, 245*, 250*, 275*, 290*, 305*, 310, 315, 335, 340, 360, Steiger 335*, 350*, 385, 435, 485, 500*, 535,550*	4.528"	115mm		KR-70M	27838	WNDH-DADHI-KR0070M






\* These models have been produced w/ more than one axle diameter. Please Verify axle diameter w/ customer before ordering.

	Tractors	Axle Diameter		Tractor Axle	INSERT NEEDED		
		IN	MM		INSERT CODE	WOLD CODE	WOLD PART NUMBER
<b>Case 4WD Scrapper</b>	STX275, STX280*, STX325, STX330*, Steiger 335*	4"	101.6mm		N/A	N/A	N/A
	STX280*, STX330*, STX375, STX425, STX440, STX450, Steiger 335* / 385 / 435 / 485 / 500 / 535 / 540	4.528"	115mm		N/A	N/A	N/A
<b>Fendt</b>	712**, 714**, 716**	3¾"	95.25mm		KR-30M	27829	WNDH-DADHI-KR0030M
	822, 824, 826, 828, 920, 922, 924, 926, 927, 930, 933, 936, 939	4.331"	110mm		KR-80110M	27853	WNDH-DADHI-KR80110M
	712**, 714**, 716**, 718, 720, 722, 724, 815, 817, 818, 820	3¾"	95mm		KR-3530M	27852	WNDH-DADHI-KR3530M
<b>Kubota</b>	M7-131†, M7-151†, M7-171†	3.937"	100mm		KR-11M	64530	WNDH-DADHI-KR0011M
	M8-191, M8-211	4.13"	105mm		KR-31M	27831	WNDH-DADHI-KR0031M
<b>International Harvester</b>	M, MD, SUPER M, SUPER MD, HYDRO 84, 300*, 400, 450, 504, 544, 560, 574, 584, 595, 656, 666, 674, 684, 685, 686, 695, 784, 884, 885, 895	2¾"	69.85mm		N/A	N/A	N/A
	SUPER 100, HYDRO 186, TURBO 186, 706, 756, 766, 786, 806, 826, 856, 866, 966, 986, 1026, 1066, 1206, 1256, 3088, 3288, 3388, 3488, 3588, 3688, 3788, 4366, 4386*, 6388, 6588, 6788	3¾"	82.55 mm		N/A	N/A	N/A
	1086, 1456, 1466, 1468, 1486, 4386*, 4568, 4586, 5088	3½"	88.9mm		N/A	N/A	N/A
	1566, 1568, 1586, 4786, 5288, 5488, 7288, 7488	4"	101.6mm		N/A	N/A	N/A

\* These models have been produced w/ more than one axle diameter. Please Verify axle diameter w/ customer before ordering.

\*\*These models have been produced with two different axle configurations, but with the same axle diameter. Verify that it is a straight or tapered keyway.

†These models do not work with 1000 series hub.

	Tractors	Axle Diameter		Tractor Axle	INSERT NEEDED		
		IN	MM		INSERT CODE	WOLD CODE	WOLD PART NUMBER
<b>New Holland &amp; Ford</b>	(Wedge Type Axle) 8000**, 8530, 8539, 8600, 8630, 8700, 8730, 9000**, 9600, 9700, TW5, TW10, TW15, TW20, TW25	3 3/8"	85.725mm		N/A	N/A	N/A
	8670, 8670A, TM120, TM130, TM140, TM155, TS100A, TS115A, TS125A, TS130A, TS135A, 8830, TW30, TW35, T6010, T6020, T6030, T6040, T6050, T6060, T6070, T6080, T6.140, T6.145, T6.150, T6.155, T6.160, T6.165, T6.175, T6.180, T7.170, T7.175, T7.185, T7.190, T7.200, T7.210, TS6.110, TS6.120, TS6.125, TS6.130, TS6.140	3 3/8"	92.075mm		KR-2920M	27851	WNDH-DADHI-KR2920M
	8160, 8260, 8360, 8560, TM115, TM125, TM135, TM150, TM165	3 3/4"	95.25mm		KR-30M	27829	WNDH-DADHI-KR0030M
	TG210, TG215, TG230, TG245, TG255*, TG275*, TG285*, TG305*, TJ275, TJ280, TJ325, TJ330, T8010, T8020, T8030*, T8040*, T8275, T8300*, T8330*, T9020, T8.275, T8.300, T8.320*, T8.330*, T8.350*	4"	101.6mm		KR-50M	27833	WNDH-DADHI-KR0050M
	T8030*, T8040*, T8050, T8300*, T8330*, T8360, T8390, T9030, T9040, T9050, T9060, T9390*, T9450*, T9505*, T9615*, T9670*, T8.320*, T8.330*, T8.350*, T8.360, T8.380, T8.390, T8.410, T8.435, TG255*, TG275*, TG285*, TG305*, TJ375, TJ380, TJ430, TJ440, TJ450, TJ480, TJ530	4.528"	115mm		KR-70M	27838	WNDH-DADHI-KR0070M
	8770, 8770A, 8870, 8870A, 8970, 8970A, T7030, T7040, T7050, T7060, T7070, T7.230, T7.235, T7.245, T7.250, T7.260, T7.270, T7.290, T7.315, TM175, TM190	4.13"	105mm		KR-31M	27831	WNDH-DADHI-KR0031M
<b>John Deere</b>	60, 70, 620, 630, 720, 730, 2240, 2350, 2355, 2440, 2520, 2550, 2555, 2640*, 2750, 2755, 2840, 2940, 2950, 2955, 3010, 3020*, 3055, 3150, 3155, 3255, 4000, 4010, 4020*, 4030*, 6105M, 6105R, 6110, 6110M, 6110R, 6115M, 6115R, 6120, 6120M, 6120R, 6125M, 6125R, 6130M*, 6130R*, 6200, 6210, 6220, 6230, 6300, 6310, 6320, 6330, 6400, 6410, 6420, 6430, 6605, 7130*, 7200*, 7210*, 7400*, 7410*, 7510*, 6615, 6715, 7230*	3 3/8"	79.375mm		KR-60MY***	27837	WNDH-DADHI-KR0060MY

\* These models have been produced w/ more than one axle diameter. Please Verify axle diameter w/ customer before ordering.

\*\* These models have been produced with two different axle configurations, but with the same axle diameter. Verify that the tractor axle is a wedge-type configuration and not a keyway-type configuration

\*\*\*This hub fits both shallow and deep keyed 3 1/8" axles.

	Tractors	Axle Diameter		Tractor Axle	INSERT NEEDED		
		IN	MM		INSERT CODE	WOLD CODE	WOLD PART NUMBER
<b>John Deere</b>	3020*, 4020*, 4030*, 4040, 4050, 4055, 4230, 4240, 4250, 4255, 4320, 4420*, 4430*, 4440*, 4455*, 6130M*, 6130R*, 6140M, 6145M, 6150M*, 7020, 7130*, 7200*, 7210*, 7220, 7230*, 7320, 7330, 7400*, 7405, 7410*, 7420, 7510*, 7520	3 <sup>3</sup> / <sub>8</sub> "	85.725mm		KR-16MY	27820	WNDH-DADHI-KR0016MY
	4420*, 4430*, 4440*, 4450, 4455*, 4520, 4620, 4630*, 5010, 5020, 6030, 6140R, 6145R, 6150M*, 6150R, 6155M, 6155R, 6170M, 6175M, 6195M, 7400*, 7410*, 7430, 7510*, 7530, 7600, 7610, 7700, 7710, 7720*, 7800, 7810, 7820*, 8630*	3 <sup>5</sup> / <sub>8</sub> "	92.075mm		KR-20MY	27823	WNDH-DADHI-KR0020MY
	4555, 4560, 4630*, 4640, 4650, 4755, 4760, 4840, 4850, 4955, 4960, 6170R*, 6175R, 6190R*, 6195R, 6210R*, 6215R, 7200R, 7210R*, 7215R, 7230R*, 7630, 7720*, 7730, 7820*, 7830, 7920, 7930, 8100*, 8110*, 8120*, 8130*, 8200*, 8210*, 8220*, 8230*, 8225R*, 8235R*, 8245R*, 8260R*, 8270R*, 8285R*, 8295R*, 8300, 8310*, 8320*, 8330*, 8370R*, 8400, 8410, 8420*, 8430*, 8850, 8870*, 8960, 8970, 9120*, 9200*, 9220*, 9230*, 9300*	3.937"	100mm		KR-100MY	27843	WNDH-DADHI-KR0100MY
	6170R*, 6190R*, 6210R*, 7210R*, 7230R*, 7250R*, 7260R*, 7270R*, 7280R*, 7290R*, 7310R*, 8100*, 8110*, 8120*, 8130*, 8200*, 8210*, 8220*, 8230*, 8225R*, 8235R*, 8245R*, 8260R*, 8270R*, 8285R*, 8295R*, 8300, 8310*, 8320*, 8330*, 8370R*, 8400, 8410, 8420*, 8430*, 8850, 8870*, 8960, 8970, 9120*, 9200*, 9220*, 9230*, 9300*, 9320*, 9330, 9360R*, 9370*, 9370R*, 9400, 9410R*, 9420*, 9420R*, 9430	4.331"	110mm		KR-110MY	27846	WNDH-DADHI-KR0110MY
	7250R*, 7260R*, 7270R*, 7280R*, 7290R*, 7310R*, 8120*, 8130*, 8220*, 8225R*, 8230*, 8235R*, 8245R**, 8260R*, 8270R**, 8285R*, 8295R**, 8310R, 8320*, 8320R**, 8330*, 8335R**, 8345R**, 8360R, 8370R**, 8420*, 8430*, 8520, 8530, 9320*, 9360R*, 9370R*, 9410R*, 9420*, 9420R*, 9460R, 9470R, 9510R, 9520, 9520R**, 9530, 9560R, 9570R**, 9620, 9620R**, 9630	4.724"	120mm		KR-120MY	27847	WNDH-DADHI-KR0120MY
	8245R**, 8270R**, 8295R**, 8320R**, 8335R*, 8345R**, 8370R**, 8400R, 9520R**, 9570R**, 9620R**	4.724"	120mm		KK-120DFMY	63248	WNDH-DADHI-KK120DFMY

\* These models have been produced w/ more than one axle diameter. Please Verify axle diameter w/ customer before ordering.

\*\* These models have been produced with two different axle configurations, but with the same axle diameter. Verify that the tractor axle is a wedge-type configuration and not a keyway-type configuration










P.O. Box 129 · St. Ansgar, Iowa 50472 · 641-713-2205 · 1-800-443-9653 · Fax 641-713-4005

	Tractors	Axle Diameter		Tractor Axle Configuration	INSERT NEEDED		
		IN	MM		INSERT CODE	WOLD CODE	WOLD PART NUMBER
John Deere Scraper	9100, 9120*, 9200*, 9220*, 9230*, 9300*	3.937"	100mm		N/A	N/A	N/A
	9120*, 9200*, 9220*, 9230*, 9300*, 9320*, 9330, 9370R*, 9400, 9420*, 9420R*, 9430, 9520*	4.331"	110mm		N/A	N/A	N/A
	9320*, 9370R*, 9420*, 9420R*, 9470R, 9520, 9520R, 9530, 9570R, 9620, 9620R, 9630	4.724"	120mm		N/A	N/A	N/A
Buhler / Versatile	2145	3 <sup>5</sup> / <sub>8</sub> "	92.075mm		KR-2920M	27851	WNDH-DADHI-KR2920M
	175, 190, 195, 210, 220, 250, 260, 265, 280, 290, 295, 305, 310, 315, 2160, 2180, 2210	4.13"	105mm		KR-31M	27831	WNDH-DADHI-KR0031M
Massey Ferguson	1100, 1105, 1130, 1135, 1150, 1155, 1500, 1505, 1800, 1805, 2675, 2705, 3140, 3505, 3524, 3525, 3545, 3552, 3630, 3650, 3680*, 6180, 6280, 6290, 6475, 6480	3 <sup>1</sup> / <sub>4</sub> "	82.55 mm		KR-13M†	27816	WNDH-DADHI-KR0013M
	6614*, 6615*, 6616*, 7614, 7615*, 7616*, 7618*, 7619*, 7620*, 7622*, 7714, 7715*, 7716*, 7718*, 7719*, 7720*, 7722*	3 <sup>1</sup> / <sub>4</sub> "	82.55 mm		KR-17M		
	2745, 2770, 2775, 2800, 2805, 3660, 3670, 3680*, 3690, 8120, 8140, 8150, 8160, 8220**, 8240**, 8255**	3 <sup>3</sup> / <sub>4</sub> "	95.25mm		KR-30M	27829	WNDH-DADHI-KR0030M
	6485, 6490, 6495, 6614*, 6615*, 6616*, 7465, 7475, 7480, 7485, 7490, 7495, 7499, 7615*, 7715*, 7616*, 7618*, 7619*, 7620*, 7622*, 7624*, 7626*, 7716*, 7718*, 7719*, 7720*, 7722*, 7724*, 8220**, 8240**, 8255**	3 <sup>3</sup> / <sub>4</sub> "	95mm		KR-3530M	27852	WNDH-DADHI-KR3530M
	4840, 4880, 4900	4"	101.6mm		N/A	N/A	N/A
	6497, 6499, 7624*, 7626*, 7724*, 7726, 8245, 8250, 8260, 8270, 8280, 8450, 8460, 8470, 8480, 8650, 8660, 8670, 8680, 8690, 8727, 8730, 8732, 8735, 8737	4.331"	110mm		KR-80110M	27853	WNDH-DADHI-KR80110M
McCormick	MTX110, MTX120, MTX125, MTX135, MTX140, MTX150, MTX155*, XTX145, XTX165	3 <sup>1</sup> / <sub>2</sub> "	88.9mm		KR-25M	27825	WNDH-DADHI-KR0025M
	MTX155*, MTX165, MTX175, MTX185, MTX200, TTX190, TTX210, TTX320, XTX185, XTX200, XTX215	4"	101.6mm		KR-50M	27833	WNDH-DADHI-KR0050M
	ZTX230, ZTX260, ZTX280	4.331"	110mm		KR-80110M	27853	WNDH-DADHI-KR80110M

\* These models have been produced w/ more than one axle diameter. Please Verify axle diameter w/ customer before ordering.

\*\*These models have been produced with two different axle configurations. Verify if it has a straight or tapered keyway.

†To install hub it may require key #1163 for the axle.

	Tractors	Axle Diameter		Tractor Axle	INSERT NEEDED		
		IN	MM		INSERT CODE	WOLD CODE	WOLD PART NUMBER
<b>Heston &amp; Fiat</b>	1180, 1180DT, 1380, 1380DT, 1580, 1580DT, 1880, 1880DT, 130-90, 130-90DT, 140-90, 140-90DT, 160-90, 160-90DT, 180-90, 180-90DT	3¾"	95.25mm		KR-30M	27829	WNDH-DADHI-KR0030M
<b>Long</b>	1340	¾"	82.55 mm		N/A	N/A	N/A
<b>Steiger</b>	WILDCAT RC210 (Order K-13 steel key for this application)	¾"	82.55 mm		KR-13M	27816	WNDH-DADHI-KR0013M
	BEARCAT 1000, COUGAR 1000, PUMA 1000	4"	101.6mm		KR-1450M	27849	WNDH-DADHI-KR1450M
<b>White &amp; AGCO White</b>	2-85, 2-88, 2-105, 2-110, 4-150, 4-175	3 ³/₁₆"	80.96mm		N/A	N/A	N/A
	6710, 6810	¾"	82.55 mm		KR-13M††	27816	WNDH-DADHI-KR0013M
	6124, 6144, 8310*, 8410*	3¾"	95.25mm		KR-30M	27829	WNDH-DADHI-KR0030M
	6125, 6145, 6175**, 6195**, 6215**, 140, 145, 160, 170, 185, 195, 2-135, 2-155, 2-180, 2-185, 4-210, 4-225, 4-270, 8310*, 8410*	3 7/₈"	98.425mm		KK-88M†	62569	WNDH-DADHI-KK0088M
	8510, 8610, 8710, 8810	4.331"	110mm		KR-80110M	27853	WNDH-DADHI-KR80110M

\* These models have been produced w/ more than one axle diameter. Please Verify axle diameter w/ customer before ordering.

\*\* These models have been produced with two different axle configurations, but with the same axle diameter. Verify that the tractor axle is a wedge-type configuration and not a keyway-type configuration

† To install hub, the two loose keys in the tractor axle must be shortened (cut off)

†† To install hubs it may require key #1163 for the axle